

CATERLUX

Live an illuminated life



10MM MAGNETIC LIGHTING SYSTEM



CATERLUX
Live an illuminated life



About us

Ever since Caterlux's inception in 2016, we have been working hard towards lighting up your homes with avant-garde quality products and exceptional service. We specialize in providing energy efficient lighting solutions and LED to our customers. Caterlux's lighting solutions add value to space be it office or home. Our lighting solutions are paving the way towards a brighter future with the combination of design and innovation. Providing quality lighting with minimal cost is what Caterlux firmly believes in.

From initial consultation to designs and conceptualization to delivering premium quality and even custom-made lighting solutions, there's nothing we don't do. All our lighting products meet the highest quality standards and are designed to give our customers absolute value for money.

Ensuring you with select, high end illumination products, we stand behind our work and guarantee the most stringent quality assurances. Caterlux lighting strives to bring to our customers lighting solutions that strike the perfect balance between quality, reliability and style.





CTR-DBXS-S006

Light Source OSRAM

Input 6W

Size 147*12*32mm

Beam Angle 24°36°

Material Aluminum

CTR-DBXS-S012

Light Source OSRAM

Input 12W

Size 294*12*32mm

Beam Angle 24°36°

Material Aluminum

CTR-DBXS-S018

Light Source OSRAM

Input 18W

Size 440*12*32mm

Beam Angle 15°25°30°60°

Material Aluminum



CTR-DBXS-M300

Light Source OSRAM

Input 8W

Size 290*12*32mm

Beam Angle Diffuse

Material Aluminum

CTR-DBXS-M600

Light Source OSRAM

Input 15W

Size 600*12*32mm

Beam Angle Diffuse

Material Aluminum

CTR-DBXS-M900

Light Source OSRAM

Input 20W

Size 900*12*32mm

Beam Angle Diffuse

Material Aluminum





CTR-DBXS-SL006

Light Source OSRAM

Input 6W

Size 147*12*65mm

Beam Angle 24°36°

Material Aluminum

CTR-DBXS-SL012

Light Source OSRAM

Input 12W

Size 294*12*65mm

Beam Angle 24°36°

Material Aluminum

CTR-DBS-1700L

Light Source OSRAM

Input 15W

Size ø40*180mm

Beam Angle 24°36°60°

Material Aluminum



CTR-DBXS-ML150

Light Source OSRAM

Input 4W

Size 147*12*65mm

Beam Angle 120°

Material Aluminum

CTR-DBXS-ML300

Light Source OSRAM

Input 8W

Size 294*12*65mm

Beam Angle 120°

Material Aluminum





MARCH

SUN	MON	TUE	WED	THU	FRI	SAT
	4	5	6	7	8	9
	11	12	13	14	15	16
	18	19	20	21	22	23
	25	26	27	28	29	30





CTR-DBXS-1700XS

Light Source OSRAM

Input 5W

Size Ø35*80mm

Beam Angle 24°36°

Material Aluminum



CTR-DBXS-1701M

Light Source OSRAM

Input 15W

Size Ø55*80mm

Beam Angle 24°36°

Material Aluminum

CTR-DBXS-1700S

Light Source OSRAM

Input 10W

Size Ø45*100mm

Beam Angle 24°36°

Material Aluminum



CTR-DBXS-1700M

Light Source OSRAM

Input 10W

Size Ø45*100mm

Beam Angle 24°36°

Material Aluminum

CTR-DBXS-P1700M

Light Source OSRAM

Input 5W

Size Ø35*300mm

Beam Angle 24°36°

Material Aluminum





CTR-DBXS-H

Length 1M/2M/3M

Size 79.2*11*12mm

Material Aluminum



CTR-DBXS-B-Z

Size 60*60*mm

Material Aluminum



CTR-DBXS-B-1

Size 60*60*mm

Material Aluminum



CTR-DBXS-H

Length 1M/2M/3M

Size L1000/L1200/1300*W45*H41mm

Material Aluminum



CTR-DBXS-C-Z

Size 60*60*mm

Material Aluminum



CTR-DBXS-C-1

Size 60*60*mm

Material Aluminum



CTR-DBXS-H

Size 79.2*11*12mm

Material Aluminum



CTR-DBXS-H

Size 79.2*11*12mm

Material Aluminum



CTR-DBXS-H1

Size 116*11*12mm

Material Aluminum



CTR-DBXS-1

Size 80*15*1.5mm

Material Aluminum



CTR-DBXS-901

Size 55*55*1.5mm


Material Aluminum



CTR-DBXS-X

Size Ø24.5*47mm

Material Aluminum



CATERLUX
Live an illuminated life



E-mail : info@caterlux.co.in
Website : www.caterlux.co.in